

### **Authorized Reseller**

Strategic 3D Solutions, Inc. 4805 Green Road, Suite 114 Raleigh, NC 27616 919-451-5963

info@strategic3dsolutions.com www.strategic3dsolutions.com

#### **EnvisionTEC GmbH**

Brüsseler Straße 51 • D-45968 Gladbeck • Germany Phone +49 2043 9875-0 Fax +49 2043 9875-99

### EnvisionTEC, Inc.

15162 S. Commerce Dr Dearborn, MI 48120 • USA Phone +1-313-436-4300 Fax +1-313-436-4303

envisiontec.com

info@envisiontec.com

# Perfactory®



### Perfactory® 4 Standard Series with ERM

EnvisionTEC's Perfactory 4 Standard Series with ERM is a low cost, easy maintenance and user friendly 3D rapid prototype manufacturing system. Using state-of-the-art Direct Light Projection technology from Texas Instruments®, the Perfactory 4 Standard Series produces the finest detail in the shortest period of time. It creates 3D models that range from the conceptual to the fully functional.

Machine Properties *	Perfactory® 4 Standard	Perfactory® 4 Standard XL
Build Envelope	6.3" x 3.9" x 7.09"/9.06" (160 x 100 x 180/230 mm)	7.6" x 4.7" x 7.09"/9.06" (192 x 120 x 180/230 mm)
Projector Resolution	1920 x 1200 Pixels	1920 x 1200 Pixels
Native Pixel Size	0.0033" (83 µm)	0.0039" (100 µm)
Pixel Size With ERM	0.0017" (42 µm)	0.0020" (50 µm)
Dynamic Voxel Resolution in Z (material dependent)**	0.0010" (25 μm) to 0.0059" (150 μm)	0.0010" (25 μm) to 0.0059" (150 μm)
Data Handling	STL	
Warranty	1 Year Included	

<sup>\*</sup> Specifications are subject to change without notice. \*\* A voxel is a volumetric pixel.

Materials Available	Ideal for	
ABStuff	General purpose similar to ABS plastic	
ABflex	General purpose similar to ABS plastic with flexible characteristics	
HTM Series	High temperature molding, architectural models, plating	
LS600, EC100, WIC 100 G, E-Shell® 200 Series	General purpose	
PIC 100	Casting	
R5, R5 Gray, R11	General purpose, master models	
RC31	High temperature applications	
Photosilver, RCP 30, RC70, RC90 (Not available on XL)	High temperature applications with fine detail	
WIC300 (Not available on XL)	General Purpose	

## System Properties

- » Build speed in constant through the build up to 1" (25 mm) at 0.0039" (100 µm) voxel thickness
- » Economic material use with no vat
- » Very few moving parts and minimal consumable components make the system user serviceable
- » Models are suitable for direct manufacturing through rapid casting
- » A choice of high quality materials are readily available
- » Material changeover can be done quickly and easily

Footprint (L x W x H): 29" x 19" x 53" (73 x 48 x 135 cm)

Weight: 188 lbs (85 kg)

Electrical Requirements: 100-120V, 5.4 Amps 220-240V, 2.4 Amps

Patents Pending

